



M.2 22110 PCIe Gen 4 x4 Enterprise SSD, 3.84TB

Reliable and blazing fast Enterprise SSD for tactical edge servers

Features

Capacity: 3.84TB

Form Factor: M.2 22110

PCIe Interface: PCIe Gen 4 x4

PCIe Gen 4x4 lane & backward compatible to PCIe Gen 3, Gen 2, and Gen 1

8 IO queues supported (1 admin queue and 8 IO queue). Each IO queue support 256 entries.

HW Pfail Support Tantalum

Compliance

NVMe 1.4

PCI Express Base 4.0

RoHS compliant

Sustained Performance

Sequential Read: up to 4500 MB/s

Sequential Write: up to 1700 MB/s

Random Read: up to 400K IOPS

Random Write: up to 50K IOPS

Reliability

Mean Time Between Failure (MTBF): < 2 million hours

Uncorrectable Bit Error Rate (UBER): < 1 sector per 1017 bits read

Power Consumption

Active Write (Max.): < 11.55 W

Active Read (Max.): < 11.55 W

Idle: < 4.2 W

Temperature Range

Operation: 0°C ~ 70°C

Storage: -40°C ~ 85°C

Environment Specifications


Commercial grade temperature & humidity test

Shock: 1500G/0.5ms

Vibration: 20Hz~80Hz/1.52mm 80Hz~2000Hz/20G

Drop: 80cm height/each face

Thermal cycling: -40°C-85°C/1000 cycles with 50% cumulative failure. (IPC-9701)




Part Number

DIG-P4M22G35-03840 D

Specifications

Feature	Specification
Part Number	DIG-P4M22G35-03840 D
Product Name	M.2 22110 PCIe Gen 4 x4 NVMe Enterprise SSD, 3.84TB
Technical Support	Your investment in DIGISTOR products is backed up by our free technical support for the lifetime of the product. If you need to contact us for any reason, visit digistor.com/support .



Contact Us
1000 SE Tech Center Dr
Suite 160
Vancouver, WA 98683

Website: digistor.com
Sales: +1 (360) 816-1800 x2051
Tech Support: +1 (360) 816-1800 x2050
Sales: sales@digistor.com, sales@cdsg.com
Support: support@digistor.com